## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (currently amended) A method of providing location-based reference information in a wireless network, comprising:

receiving an information telephone call from a subscriber device, a telephone number initiating said telephone call including said information telephone call comprising dialed digits "4-1-1" suffixed by at least one auxiliary digit suffixed by to an end of said telephone number before transmission of said telephone number;

querying a location-based wireless service in response to said <u>information</u> telephone call to automatically obtain a current location of said subscriber device;

retrieving a location based message associated with said obtained current location and selected using said at least one auxiliary digit suffixed to said end of said telephone number; and

transmitting said retrieved location based message to said subscriber device.

2. (currently amended) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

at least two auxiliary digits are suffixed to said end of said <u>dialed</u> <u>digits "4-1-1" telephone number</u>.

3. (currently amended) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said information telephone call is initiated with <u>said</u> dialed digits "4-1".

4. (previously presented) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said current location of said subscriber device is obtained using wireless or cellular network signaling.

## 5. (canceled)

6. (previously presented) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said current location of said subscriber device is determined using an angle of arrival of a wireless signal from said subscriber.

7. (previously presented) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said current location of said subscriber device is determined using a network generated location based on a centroid of a cell site sector's radio frequency (RF) polygon.

8. (previously presented) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said current location of said subscriber device is determined using a time difference of arrival of wireless signals from said subscriber.

9. (previously presented) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said current location of said subscriber device is determined using time of arrival of a wireless signal from said subscriber.

10. (previously presented) The method of providing location-based reference information in a wireless network according to claim 1, wherein:

said current location of said subscriber device is determined using a known location of a cell/sector servicing said subscriber.

11. (currently amended) A method of providing location-based reference information in a wireless network, comprising:

receiving, at a mobile switching center, an information telephone call from a subscriber device, a telephone number initiating said telephone call including said information telephone call comprising dialed digits "4-1-1" suffixed by at least one auxiliary digit suffixed to an end of said telephone number before transmission of said telephone number;

querying a location-based wireless service in response to said telephone call to automatically obtain a current location of said subscriber device;

retrieving a location based message associated with said obtained current location and selected using said at least one auxiliary digit suffixed to said end of said telephone number; and

transmitting said retrieved located based message to said subscriber device.

12. (currently amended) The method of providing location-based reference information in a wireless network according to claim 11, wherein:

at least two auxiliary digits are suffixed to said end of said dialed digits "4-1-1" telephone number.

- 13. (currently amended) The method of providing location-based reference information in a wireless network according to claim 11, wherein: said information telephone call is initiated with <u>said</u> dialed digits "4-1-1".
- 14. (previously presented) The method of providing location-based reference information in a wireless network according to claim 11, wherein: said current location of said subscriber device is obtained using wireless or cellular network signaling.

## 15. (canceled)

16. (previously presented) The method of providing location-based reference information in a wireless network according to claim 11, wherein:

said current location of said subscriber device is determined using an angle of arrival of a wireless signal from said subscriber.

- 17. (previously presented) The method of providing location-based reference information in a wireless network according to claim 11, wherein:
- said current location of said subscriber device is determined using a time difference of arrival of wireless signals from said subscriber.
- 18. (previously presented) The method of providing location-based reference information in a wireless network according to claim 11, wherein:

said current location of said subscriber device is determined using time of arrival of a wireless signal from said subscriber.

19. (previously presented) The method of providing location-based reference information in a wireless network according to claim 11, wherein:

said current location of said subscriber device is determined using a known location of a cell/sector servicing said subscriber.

- 20. (currently amended) A system to provide location-based reference information in a wireless network, comprising:
- a receiver to receive an information telephone call from a subscriber device, a telephone number initiating said telephone call including said information telephone call comprising dialed digits "4-1-1" suffixed by at least one auxiliary digit suffixed by to an end of said telephone number before transmission of said telephone number;
- a location-based wireless service queried in response to said received <u>dialed digits "4-1-1"</u> telephone number to automatically obtain a current location of said subscriber device;
- a retriever to retrieve a location based message associated with said obtained current location and selected using said at least one auxiliary digit suffixed to said end of said telephone number; and
- a transmitter to transmit said retrieved location based message to said subscriber device.
- 21. (currently amended) The system to provide location-based reference information in a wireless network according to claim 20, wherein:

at least two auxiliary digits are suffixed to said ond of said dialed digits "4-1-1" telephone number.

22. (currently amended) The system to provide location-based reference information in a wireless network according to claim 20, wherein:

said information telephone call is initiated with <u>said</u> dialed digits "4-1-1".

23. (currently amended) A system to provide location-based reference information in a wireless network, comprising:

a receiver integrated with a mobile switching center to receive an information telephone call from a subscriber device, a telephone number initiating said telephone call including said information telephone call comprising dialed digits "4-1-1" suffixed by at least one auxiliary digit suffixed by to an end of said telephone number before transmission of said telephone number;

a location-based wireless service queried in response to said received telephone call to automatically obtain a current location of said subscriber device;

a retriever to retrieve a location based message associated with said obtained current location and selected using said at least one auxiliary digit suffixed to said end of said telephone number; and

a transmitter to transmit said retrieved location based message to said subscriber device.

24. (currently amended) The system to provide location-based reference information in a wireless network according to claim 23, wherein:

at least two auxiliary digits are suffixed to said-end-of said dialed digits "4-1-1" telephone number.

25. (currently amended) The system to provide location-based reference information in a wireless network according to claim 23, wherein:

said information telephone call is initiated with <u>said</u> dialed digits "4-1-1".

26. (currently amended) A system to provide location-based reference information in a wireless network, comprising:

means for receiving an information telephone call from a subscriber device, a telephone number initiating said telephone call including said information telephone call comprising dialed digits "4-1-1" suffixed by at least one auxiliary digit suffixed by to an end of said telephone number before transmission of said telephone number;

means for querying a location-based wireless service in response to said telephone call to automatically obtain a current location of said subscriber device;

means for retrieving a location based message associated with said obtained current location and selected using said at least one auxiliary digit suffixed to said end of said telephone number; and

means for transmitting said retrieved location based message to said subscriber device.

27. (currently amended) The system to provide location-based reference information in a wireless network according to claim 26, wherein:

at least two auxiliary digits are suffixed to said end of said dialed digits "4-1-1" telephone number.

28. (currently amended) The system to provide location-based reference information in a wireless network according to claim 26, wherein:

said information telephone call is initiated with <u>said</u> dialed digits "4-1-1".

29. (currently amended) A system to provide location-based reference information in a wireless network, comprising:

means for receiving an information telephone call from a subscriber device, a telephone number initiating said telephone call including said information telephone call comprising dialed digits "4-1-1" suffixed by at least one auxiliary digit suffixed by to an end of said telephone number before transmission of said telephone number;

means for querying a location-based wireless service in response to said telephone call to automatically obtain a current location of said subscriber device;

means for retrieving a location based message associated with said obtained current location and selected using said at least one auxiliary digit suffixed to said end of said telephone number; and

means for transmitting said retrieved location based message to said subscriber device.

30. (currently amended) The system to provide location-based reference information in a wireless network according to claim 29, wherein:

at least two auxiliary digits are suffixed to said end of said dialed digits "4-1-1" telephone number.

31. (currently amended) The system to provide location-based reference information in a wireless network according to claim 29, wherein:

said information telephone call is initiated with <u>said</u> dialed digits "4-1".